



standard diving sleeve resistance thermometer Pt-100 with and without neck tube

Description

Fundamentals of ACS Universal RTD standardized, high-quality platinum resistance form of a nominal resistance of 100 ohms at 0 ° C, tolerance classes A, B, 1/3B (AA) - in accordance with DIN EN / IEC 60751st.

ACS Pt100 probes are characterized by high accuracy and reproducibility are made and extremely reliable. The sensing elements are embedded in the protective tube with magnesium oxide powder and sealed hermetically. Thus, a good heat transfer and vibration protection is achieved.

Standard measuring temperatures are -70 ° C. .. +300 ° C;

High temperature versions +500 ° C / +600 ° C, low-temperature versions, special materials, special process connections, OEM versions are also available.

The given measuring temperature refers to an average temperature at the probe tip.

With cable versions, for example PTS / PTK and Pt100 sensors with connection head, possibly with integrated head transmitter, must be based on the respective maximum

temperature of the cable, heads, etc., with on-site isolation, use of Pt100 be used with extension into account. The measurement speed of the individual Pt100 sensor is highly dependent on operating conditions, the measured medium and the physical dimensions.

The immersion depth should be not less than 50 mm. Shorter probe lengths clarify please always experienced with the ACS staff.



Technical data	
Measuring element:	Platinum resistance element Pt100/Pt1000, others by request
Temperature ranges:	at measurement tip: -70°C...+300°C +500°C/ +600°C and low temperature versions by request
Tolerance:	AA, A, B - according to IEC 60751
Signal type:	- 1x Pt100: in 2-, 3-, 4-wire-switch
	- 2x Pt100: in 2x 2-wire or 2x 3-wire-switch
	- 3x Pt100: in 3x 2-wire-switch
Connection:	- with flying leads for head transmitter mounting
	- head transmitter, 4...20 mA/ 0...10 V output, Standard, Ex, Profibus; others by request
Materials	- connection area made out of aluminium, plastic or stainless steel
	- fixed connection cable - PTFE shielded, silicone, PVC, glass silk protected with steel mesh, others by request - Lemo-plug system, M12 plug system
Materials (terms of process):	- protection tubes made of seamless stainless steel: 1.4571 (AISI 316Ti) - flanges, process connections: 1.4571 (AISI 316 Ti) - special materials by request
Materials (terms of connection):	- housing: aluminium, CrNi-steel, PP-polypropylene, POM-polyoxymethylene - cable material -> see „connection“

